

Loway
r e s e a r c h

QueueMetrics
call center monitor

QLOADER USER MANUAL

QLOADER USER MANUAL

V1.0, Loway

Table of Contents

- 1. Loading the queue_log file into MySQL with Qloaderd 1
 - What is Qloaderd? 1
 - Installing qloaderd 1
 - Starting qloaderd init-style on RH-based systems 2
 - Starting qloaderd init-style on other systems 3
 - Advanced topics 3
 - Heartbeat 3
 - Subqueues 3
 - Agent rewriting 4
 - Database-driven agent rewriting 5
 - Debugging qloaderd 5
 - qloader and queue_log rotation 5
 - Getting help 6
- 2. Data Queue Partial Update 7
 - Configuration 7
 - How to use it 7

Chapter 1. Loading the queue_log file into MySQL with Qloaderd

Note

this is not a tutorial on how to use MySQL storage in QueueMetrics. Such a topic is covered in detail in QueueMetrics' User Manual

What is Qloaderd?

Qloaderd is a small scripts that uploads queue_log data into a MySQL database for further analysis by <http://queuemetrics.com> . It is designed to be used instead of the older queueLoader.pl script, and offers a number of advantages over the older version:

- qloaderd is designed to be a one-stop solution to upload data. No need for tail or custom startup scripts.
- qloaderd is able to upload only data that is missing from the given partition, by checking the timestamp and the row's contents in order to prevent duplicate rows. This way you every time it is started, it will update the MySQL table with all data that is missing from it and then will start tailing the queue_log file for variations.
- In the case of a database problem or a disconnection, qloaderd will keep retrying to connect to the database until it succeeds. No data is lost if the database goes offline for a while.
- qloaderd will automatically detect invalid queue_log lines and will skip them immediately
- qloaderd keeps a detailed log of all its activity
- qloaderd can be installed as a service using a simple startup script
- In order to avoid service disruptions due to a lost database connection and to confirm QueueMetrics the connection is alive, qloader will periodically insert heartbeat information in the queue_log database.

Installing qloaderd

To install qloaderd, copy the file qloader.pl to a location of your choice (we suggest /usr/local/qloader). Run the following commands to make sure the file is executable:

```
dos2unix qloader.pl
chmod a+x qloader.pl
```

If you run a yum-based Linux distro, you can also have qloaderd installed automatically by issuing:

```
wget -P /etc/yum.repos.d http://yum.loway.ch/loway.repo
yum install qloaderd
```

You will still have to update it manually in order to configure it correctly.

You now have to edit the qloader.pl file in order to set up your database connection, by changing the following parameters:

```
my $mysql_host = "myserver.mylan";  
my $mysql_db   = "queuemetrics";  
my $mysql_user = "username";  
my $mysql_pass = "password";
```

The qloader script expects three parameters to run:

- The first parameter is the full path to the queue_log file it has to upload
- The second parameter is the partition into which it will upload data
- The third parameter is the log file it will create when running

To test that the qloader script is working, try the following command:

```
./qloader.pl /var/log/asterisk/queue_log P02 /var/log/asterisk/qloader.log
```

This command will try uploading the contents of the file `/var/log/asterisk/queue_log` to partition `P02` of the chosen database, writing its own log on `/var/log/asterisk/qloader.log`. When the program is running no output is written on stdout; if you want to know how the loading is going you have to consult its own log file.

Optionally, you can pass along one or more of the following command line parameters before the mandatory parameters:

- `-h hostname`: the MySQL hostname to connect to
- `-d database`: the MySQL database to connect to
- `-u user`: the MySQL username to use
- `-p pass`: the MySQL password to use

The parameters above override the settings edited in `qloader.pl`. Please note that it's not advisable to pass the MySQL password on the command line.

Starting qloaderd init-style on RH-based systems

We provide a script (`qloaderd`) that can be put into `/etc/init.d` in order to start and stop qloader as a service and have it start automatically when the machine boots. You will find it in the *Redhat-style-initscripts* directory. The file is called `qloaderd` and must be put into `/etc/init.d` on the Asterisk server. It was made for RHEL/CentOS/AAH/Trixbox, but it will likely work on most similar versions of Linux.

Run the following commands to make sure the file is executable:

```
dos2unix /etc/init.d/qloaderd  
chmod +x /etc/init.d/qloaderd
```

You then need to create a configuration file under `/etc/sysconfig/qloaderd` that will look like the following one:

```
PARTITION=P001  
QUEUELOG=/var/log/asterisk/queue_log  
LOGFILE=/var/log/asterisk/qloaderd.log
```

```
LOCKFILE=/var/lock/subsys/qloaderd
PIDFILE=/var/run/qloaderd.pid
```

```
MYSQLHOST=localhost
MYSQLDB=queuemetrics
MYSQLUSER=queuemetrics
MYSQLPASS=javadude
```

You usually only need to modify the PARTITION and maybe QUEUELOG entries.

At this point, you can start the qloader simply by typing `/etc/init.d/qloaderd start` and stop it by typing `/etc/init.d/qloaderd stop`. As qloader is able to upload only missing data, no data is lost if you stop it.

In order to have the service started on boot, use the command:

```
chkconfig --add qloaderd
```

As a default, it starts automatically in runlevels 2,3,4 and 5. You can easily change that with `chkconfig`.

Starting qloaderd init-style on other systems

We also provide a plain-vanilla startup script that can be installed in your local startup directory in order to start Qloader automatically. It may require a bit of tweaking, but it will run on all Linux distributions. You will find it in the *Other-initscripts* directory. Follow the same instructions as for a RedHat based system to make the script executable and configure it.

Advanced topics

The following features of Qloaderd can be enabled or disabled as needed. Most people will not need them.

Heartbeat

Qloaderd can insert a *heartbeat* log entry in order to make sure that:

- The MySQL channel stays open all of the time, even when there is no activity on the Asterisk side. This is useful because MySQL disconnects the DB connection after a given channel inactivity (usually 8 hours) and sometimes reconnecting a dead channel will not work.
- On the QueueMetrics side, it is possible to know immediately if one or more members of a cluster have been disconnected, as the heartbeat information will be present even if Asterisk is idle

This option is turned on by default, and is controlled by the configuration option:

```
my $heartbeat_delay = 15 * 60;
```

This means the heartbeat is sent every 15 minutes after the `queue_log` is idle. If you would like to turn this off, set it to 0.

Subqueues

If you work in an environment where a single queue is used to service a number of different agents, it might be of interest to you to enable subqueues; i.e. to have the queue name rewritten appending a client code at the end, so that you can query them from QueueMetrics as if each client was serviced by a dedicated queue.

In order to activate this, you must:

- Set the line:

```
my $use_subqueue = 1;
```

- If you optionally add a comment to the client code after the "/" symbol, you should set

```
my $split_subq_name = 0;
```

to have the comment clipped off. This is useful if for debug reasons you would like the client code to be "1234/Red", where "1234" is the client code and "Red" is a human-readable comment.

- Create a table called *qlog_opencalls* in the QueueMetrics database, using the following schema:

```
CREATE TABLE `qlog_opencalls` (
  `rowId` int(10) unsigned NOT NULL auto_increment,
  `partition` varchar(20) NOT NULL default '',
  `callId` varchar(45) NOT NULL default '',
  `queue` varchar(45) NOT NULL default '',
  `subqueue` varchar(45) NOT NULL default '',
  `lastVerb` varchar(45) NOT NULL default '',
  `lastTst` int(10) unsigned NOT NULL default '0',
  `lastUpd` datetime NOT NULL default '0000-00-00 00:00:00',
  PRIMARY KEY (`rowId`),
  KEY `accIdx1` (`callId`, `partition`)
) TYPE=MyISAM;
```

- Whenever you pipe a call to the Queue() command in Asterisk, set the client code in the URL parameter of the command, like for example in:

```
exten => s,8,Queue(queue-service|t|1234||180)
```

Here the queue *queue-service* is called with a client code of *1234*; the resulting queue activity will be seen in QueueMetrics as if it was done on queue *queue-service.1234*.

Please note that you should maintain the *qlog_opencalls* table yourselves, deleting periodically rows with a 'lastUpd' timestamp over one day old and optimizing it as needed (this will be done automatically in future revisions of Qloaderd).

To achieve this result, just run the following queries through a cron job in a moment when the system is idle or is experiencing a low load:

```
DELETE FROM qlog_opencalls WHERE lastUpd < DATE_SUB( NOW(), INTERVAL 48 HOUR);
OPTIMIZE TABLE qlog_opencalls;
```

As we delete a potentially large number of rows at once, running the OPTIMIZE saves space and improves index performance as well. The downside is that it could lock the table for a few seconds.

Agent rewriting

It is possible to perform advanced channel rewriting to the *Agent/XXX* format. This is done on data loading and does not require QueueMetrics to do it again and again every time it loads data.

To enable this feature, set:

```
my $rewriteToAgent = 1; # 0 no; 1 yes
```

```
my @channelsToAgent = ( 'Local', 'SIP' );
```

The configuration above will mean that channels like SIP/1234 will be rewritten to Agent/1234, while Local/2345@agents [mailto:2345@agents] will be Agent/2345.

Database-driven agent rewriting

It is possible to use a database table to store channel rewriting rules for maximum flexibility. This is often used e.g. when using Asterisk Realtime and still wanting Agent/xxx and not SIP/yyy, where you keep track of agent xxx being dynamically logged on to SIP/yyy.

To enable this feature, set:

```
my $dbAgentRewrite = 1;
```

You should also create a table in the QueueMetrics database with the following definition:

```
CREATE TABLE `qlog_rewrite` (  
  `ag_from` varchar(50) NOT NULL,  
  `ag_rewritten` varchar(50) NOT NULL,  
  `last_upd` datetime NOT NULL,  
  PRIMARY KEY (`ag_from`)  
) ENGINE=MyISAM DEFAULT CHARSET=latin1;
```

An enter the rewrite rules as tuples (*ag_from*, *ag_rewritten*). The *last_upd* key is not used and only given as an hint of very old entries that might need deletion. Before enabling this mode, please consider that a query will be performed for *nearly every line* of the *queue_log* that is being processed. Results are not cached, as the ability to change the underlying table while *qloaderd* is running is considered a feature.

Debugging qloaderd

If you suspect problems with *qloaderd*:

- First of all, have a look at its own log file.
- Try running a queue and check that lines get loaded into MySQL in real-time. The following query will often be helpful to count all elements in your *queue_log* table:

```
select partition, queue, count(*) as n_records  
from queue_log  
group by partition, queue  
order by partition, queue
```

Note

this query runs a full table scan, so it may take a long time to complete if you have million of lines loaded.

- Run the real-time page in QueueMetrics

qloader and queue_log rotation

As *qloader* keeps reading the *queue_log* file, it must be notified when the *queue_log* file is being rotated. Sending it a */etc/init.d/qloaderd restart* after the rotation has taken place will make sure that *qloader* starts loading data from the new *queue_log* file. It would be a nice idea to rotate its own log file too.

You could modify the `/etc/logrotate.d/asterisk` file as follows:

```
/var/log/asterisk/*log {
    missingok
    rotate 5
    weekly
    create 0640 asterisk asterisk
    postrotate
        /usr/sbin/asterisk -rx 'logger reload' > /dev/null 2> /dev/null
        /etc/init.d/qloaderd restart > /dev/null 2> /dev/null
    endscript
}
```

Getting help

If you need further help in setting up qloaderd...

- First of all, have a look at the QueueMetrics FAQ [<http://queuemetrics.com/faq.jsp>]
- Then try the QueueMetrics forum [<http://forum.queuemetrics.com/faq.jsp>]
- Feel free to contact us [<http://queuemetrics.com/contact.jsp>].

Chapter 2. Data Queue Partial Update

The script is able to update the queues data activity already stored in the QueueMetrics database with a new data coming from a different queue_log. It's usefull for maintaining corrupted, or restoring, databases.

This script works in pair with the qloader.pl script **with revision number equal or greater than 1.12**.

Configuration

In order to use it, the script has to be customized with information related to the database. The relevant configuration keys are below reported:

```
my $mysql_host = "10.10.3.5";
my $mysql_db   = "queuemetrics";
my $mysql_user = "ldap";
my $mysql_pass = "ldappo";

my $qloaderbin = "./qloader.pl";

my $logfile     = "queuepartialupdater.log";
```

More in detail:

- \$mysql_host: is the server where the QM database is located
- \$mysql_db: is the QM database name
- \$mysql_user: is a QM database user with read/write permission on it
- \$mysql_pass: is the password related to the below specified user
- \$qloaderbin: is the full path where the qloader.pl script could be reached
- \$logfile: is the file where the log will be written

How to use it

The script could be called by the command line specifying:

- The queue data file to be read
- The partition to be updated
- The queue log data file (the one the qloader script will use).

The script will be responsible to remove all data overlapping with the period specified in the input queue data file for the defined partition. It will be, then, responsible to call the qloader script. That script will be able to fill the database with the new information provided by the same queue data log. At the end of the processing, the log specified by the command line will report the result of the new data filling. The log specified by the configuration, instead, will list the actions performed by the queuePartialUpdater script in order to correct the database.

An example of usage is:

```
./queuePartialUpdater.pl /var/log/asterisk/queue_log P01 /var/log/qlog.log
```